Bremswiderstand BWx150xxx

Beschreibung:

Kurzschlussfester, „eigensicherer“[1] Widerstand in Aluminiumgehäuse eloxiert, Schutzart IP65[2], zum Betrieb an Umrichtern (Bremstransistoren). Detaillierte Maße siehe technische Zeichnung (auf Anfrage).





Technische Daten (ϑ_A = 20°C, wenn nichts anderes angegeben):

Nennleistung (W)	Maße LxBxH (mm)		Widerstandswerte (Ohm)	
60 (150 bei ED = 35%, ϑ_A = 20°C)	80 x 52 x 28		11; 75; 300	
Parameter	**Symbol**	**Wert**	**Einheit**	**Bedingungen**
Toleranz		± 5	%	Raumtemperatur
Gewicht	m	ca. 0,23	kg	
Anschlusslitze	A L	1,5 (AWG16) 510±40	mm^2 mm	PTFE isoliert, UL Style 1659
Lagertemperatur	ϑ_S	-25 ... +85	°C	
Maximal zulässige Betriebsspannung	U_B	≤ 700 AC ≤ 1000 DC	V	Unter Berücksichtigung der Eigensicherheit[1]
	U_B	≤ 600 AC ≤ 848 DC	V	Unter Berücksichtigung CSA
Energieaufnahmen	E	2,2 4,4	kJ	bei 1,2s (ED 1%) bei 7,2s (ED 6%)
Isolationsspannung	U_{ISO}	≥ 4000	V	AC; f = 50 Hz; t = 1 s
Maximal zulässige Gehäusetemperatur	ϑ_C	≤ 250	°C	Freie Konvektion
Temperaturkoeffizient	TK	20 ... 100	10^{-6}/K	
Isolationswiderstand	R_{ISO}	≥ 100	MΩ	$U_{meß}$ = 1000 VDC
Induktivität	L	≤ 30	µH	f = 300 kHz, $U_{meß}$ = 50 mV
Kapazität gegen Gehäuse	C	≤ 300	pF	f = 300 kHz, $U_{meß}$ = 50 mV
Thermische Zeitkonstante	τ	ca. 550	sec	Gehäuse BWD150xxx
Maximal zulässige Drahttemperatur	ϑ_{hot}	max. + 600	°C	
Approbation				cCSAus (CSA file #210040) (basierend auf CSA-C22.2 und UL 508)

[1]: „Eigensicherheit:“
Bei vierfacher Typleistung und freier Konvektion
1. Kein Kurzschluss
2. Kein Körperschluss
3. Selbstverlöschend
4. Kein Schmelzen des Gehäuses

Hinweis:
Bei Montagen im Wärmestau können Gehäusetemperaturen bis 350°C erreicht werden

[2]: Prüfbedingungen: Wasserstrahl aus Düse 6,3mm Innendurchmesser, Volumenstrom 12,5l/min +/- 5%, Wasserdruck entsprechend Volumenstrom, Abstand 2,5-3m, Prüfdauer 3min

Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com

Weitere Ausführung

BWS150 mit Flachsteckhülse



Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com

Impulsbelastbarkeit BWx150xxx

(ohne Einschränkung der Lebensdauer)



Alle Einsatzfälle links unterhalb der Kurven können durch diese Bremswiderstände abgedeckt werden.

Rahmenbedingungen:

1. Basis ist die übliche Zykluszeit von 120 Sekunden.
2. Die Gehäusetemperatur kann über das beiliegende Temperaturdiagramm anhand der mittleren Leistung ermittelt werden. Die mittlere Leistung errechnet sich nach der Formel P_m = P[W] x ED[%] / 100. Der im Schaubild „Gehäusetemperatur Bremswiderstand ...“ abgelesene Wert zuzüglich 5K ergibt die Gehäusetemperatur bei der entsprechenden Impulsleistung.

Gehäusetemperatur BWx150xxx

(bei Einschaltdauer ED = 100%, Max. zulässige Temperatur T = 250°C)



Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com

Brake resistor BWx150xxx

Description:

Short-circuit-proof, self-protecting[1)] in anodized aluminium casings, protection class according to IP65[2)], for operation on converters (brake transistors). For detailed dimensions refer to the technical drawing (on request).





Technical data (ϑ_A = 20°C, if nothing else is stated):

Nominal capacity (W)	Dimensions LxWxH (mm)		Resistance values (Ohm)	
60 (150 at ED = 35%, ϑ_A = 20°C)	80 x 52 x 28		11; 75; 300	
Parameters	**Symbol**	**Value**	**Unit**	**Conditions**
Tolerance		± 5	%	room temperature
Weight	m	approx 0,23	kg	
Connecting wire	A L	1,5 (AWG16) 510±40	mm^2 mm	PTFE isolated, UL Style 1659
Storing temperature	ϑ_S	-25 ... +85	°C	
Max. permissible operating voltage	U_B	≤ 700 AC ≤ 1000 DC	V	considering "self-protection"[1)]
	U_B	≤ 600 AC ≤ 848 DC	V	considering CSA
Energy consumption	E	2,2 4,4	kJ	with 1,2s (1% ED) with 7,2s (6% ED)
Insulation voltage	U_{ISO}	≥ 4000	V	AC; f = 50 Hz; t = 1 s
Max. permissible casing temperature	ϑ_C	≤ 250	°C	free convection
Temperature coefficient	TK	20 ... 100	10^{-6}/K	
Insulation resistance	R_{ISO}	≥ 100	MΩ	U_{MEAS} = 1000 VDC
Inductance	L	≤ 30	µH	f = 300 kHz, U_{MEAS} = 50 mV
Capacity against housing	C	≤ 300	pF	f = 300 kHz, U_{MEAS} = 50 mV
Thermic time factor	τ	Approx 550	sec	Casing BWD150xxx
Max. permissible wire temperature	ϑ_{hot}	max. + 600	°C	
Approbation				cCSAus (CSA file# 210040) (both based on CSA-C22.2 and UL 508)

1): Self-protection:

At four time type capacity and free convection
1. No short circuit
2. No fault to frame
3. Self-extinguishing
4. No melting of casing

Warning:
Mounted in areas without free air change surface no fire temperatures up to 350 degrees Celsius can be reached.

2): Test conditions: Water jet from nozzle 6,3mm inside diameter, flow rate 12,5l/min +/-5%, water pressure according to volume flow, distance 2,5-3m, test duration 3min

Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com

Further versions

BWS150 with flat pin bushing



Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com

Pulse carrying capacity BWx150xxx

(without limitation the endurance)



This brake resistors cover any operation requirement in the range below the curve.

General set up:

1. Fundamentally, the usual cycle time is 120 seconds.
2. The casing temperature can be determined applying the average performance on the included temperature diagram. The average performance can be determined as follows: Pm = P[W] x ED[%] /100. If you add 5K to the respective value in the temperature diagram, you will have the casing temperature in respect to the pulse capacity.

Housing temperature BWx150xxx

(At an ON-period ED = 100%, Maximum temperature = 250°C)



Michael Koch GmbH, Zum Grenzgraben 28, 76698 Ubstadt-Weiher, Germany, Tel.: +49 7251 9626200
mail@bremsenergie.de, www.bremsenergie.de, mail@brakeenergy.com, www.brakeenergy.com